

3M™ Wall Panel System featuring 3M™ DI-NOC™ Architectural Finishes

Technical Data Sheet
Release A, Effective February 2012

Innovate Commercial Interior Spaces with 3M

Dramatically change the look of existing environments with ease using 3M™ Wall Panel Systems featuring 3M™ DI-NOC™ Architectural Finishes.

- Core made from 100% recycled wood fiber
- 500+ designs available
- 3M Wall Panel System — Ready to install with supporting components
- Surface Protective Overlayer — Provides surface protection; Refer to abrasion testing in Physical Characteristics below
- Surface Protective Overlayer — Minimizes the appearance of fingerprints
- Custom finish patterns upon request



3M DI-NOC Architectural Finishes



Before



After — 3M Wall Panel in 3M DI-NOC Architectural Finish FW-233

Inspire Design with Flexibility — Renew and Refresh Interior Wall Systems with 3M

3M Wall Panel System featuring 3M DI-NOC Architectural Finishes Options

Textures	Texture Designs	Applications	Woods	Wood Designs	Applications
Abstract	Various	Flexible Finish Films for MDF, Metal, Select Sculpted Panels	Fine Wood	Fine Wood, Metallic Wood	Flexible Finish Films for MDF, Metal, Select Sculpted Panels
Naturals	Stone, Weave*, Sand, Stucco, Leather	Flexible Finish Films for MDF, Metal, Select Sculpted Panels	Wood Grains	Wood Grain, Wood Grain Gloss	Flexible Finish Films for MDF, Metal, Select Sculpted Panels
Metallics	Metallic*, Carbon, Little Weave, Random Style*, G-Emboss*	Flexible Finish Films for MDF, Metal, Select Sculpted Panels	—	—	—
Pure Color	Solid, High Gloss*	Ideal Finish — Exceeds Conventional Solutions	—	—	—
Custom Designs	Upon Request	Sample Needed for Matching	Custom Designs	Upon Request	Sample Needed for Matching

* For Flat Panels Only

** See 3M™ DI-NOC™ Architectural Finishes Catalog or 3MArchitecturalMarkets.com for design options.

3M™ Wall Panel Systems contain 100% recycled wood fiber without any formaldehyde or urea formaldehyde added and a low VOC finish.



Physical Characteristics

Characteristics	Description
Material	3M™ Wall Panel Systems are composed of a vinyl film applied to wood panel with 100% recycled fiber content
Finishes	Over 500 3M™ DI-NOC™ Architectural Finish designs are available See www.3MArchitecturalMarkets.com
Thickness	1/2" (13mm) board with 8.5 mil (0.212mm) Architectural Finish 3/4" (19mm) board with 8.5 mil (0.212mm) Architectural Finish
Weight	2-1/4 lbs/sq ft for 1/2" board 2-3/4 lbs/sq ft for 3/4" board
LEED Points	3M Wall Panel Systems may contribute to Project LEED® Rating System LEED Project Officials to determine outcomes
Sizes	Standard sizes up to 4 ft x 8 ft are available Custom sizes available upon request
Flammability	Wall Board — Class A Fire Rated (ASTM E-84) 3M DI-NOC Architectural Finishes — Class A Fire Rated (ASTM E-84)
Abrasion Resistance	7,000 cycles with no wear through of surface finish (JIS K7204) CS-17 wheel, loading weight 1 kg

All natural wood products vary in color and grain.

Attachment Systems

Standard system includes z-bar and z-clip type hardware. Attachment systems may vary by project.

Cleaning Wall Panels

To clean the surface of the 3M Wall Panel System, use a clean, soft cloth with mild detergent and water. Hot water may be required for heavier soil.

Storage and Shipping

Custom machine cuts per supplied shop drawings. Store products in a clean, dry place out of direct sunlight. Store products in a space where the ambient temperature and humidity conditions are being maintained at levels indicated for the project when occupied for its intended use. Handle products carefully to avoid chipping edges or damage to 3M DI-NOC Architectural Finish.

Warranty

Please refer to 3M Wall Panel System featuring 3M DI-NOC Architectural Finishes warranty document.

Note: USGBC does not certify, promote or endorse products and services of individual companies. 3M Wall Panel Systems featuring 3M DI-NOC Architectural Finishes may contribute to project LEED points. LEED project officials interpret how solutions may impact project rating system.



**3M Architectural Markets
3M U.S.**
3M Center
Building 220-7W-07
St. Paul, MN 55144-1000
1-888-650-3497
3MArchitecturalMarkets.com

**3M Architectural Markets
3M Canada**
1840 Oxford St E
London, ON N5V 3R6
1-800-265-1840

**Architectural Markets Department
3M Europe**
Hermeslaan 7
1831 Diegem
Belgium
www.3M.eu/ArchitecturalMarkets

**3M Architectural Markets
3M Italia S.p.A.**
Via Norberto Bobbio, 21
20096 Pioltello MI
Tel 02.7035.2517
www.dubic.it

**3M India Limited
Architectural Markets Department**
Concorde Blook, UB City
24 Vittal Mallya Road, Bangalore-560 001
Tel: 080 2223 1414
Fax: 080 2223 1450
3minteriors.in@mmm.com
www.3M.com/in/interiors
www.spacesunleased.com

Please recycle. Printed in U.S.A.
© 3M 2012. All rights reserved.
98-0406-0012-8

3M and DI-NOC are trademarks of
3M Company. LEED is a registered
trademark of USGBC.