

Physical Properties:	Total Weight	U.S. Units	Metric Units
		24.0 oz./LY	744 G/PLM
		16.0 oz./SY	543 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 27" x Vertical 18"	

Federal Specifications: DeNovo Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 10; Smoke Developed: 20

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed exclusively with water-based, low VOC inks
- Microventing for permeability is available on a custom order basis
- Five year warranty against materials defects

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability
- CA Prop 65 compliant

Permeability, Moisture and Mold:

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free™ Micro-vented wallcovering from DeNovoWall can be used to help control un-wanted moisture inside a building envelope.

INSTALLATION NOTE

Cibolo™ is a random match / reversible pattern
For specifications and hanging instructions go to: www.denovowall.com