

Mokara™

de novo® WALL

Type II

Physical Properties:	Total Weight	U.S. Units	Metric Units
		24.0 oz./LY	744 G/PLM
		16 oz./SQ	543 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 54" x Vertical 18"	

Federal Specifications: Meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

Fire Hazard Classification Results: **ASTM E-84** Tunnel Test: Class A, Flame Spread: 5; Smoke Developed: 15
Passes NFPA 286 Corner Burn Test
Tested in accordance with **CAN/ULC S102.-10**

Performance Features:

- Phthalate-free
- No heavy metals or formaldehyde
- Printed with low VOC inks
- Five year warranty against materials defects

Environmental Attributes:

- Ultra-low emitting – Pass rating under CA 01350
- NSF/ANSI 342 certified for sustainability

Permeability, Moisture and Mold:

Contains anti-microbial additives to resist the grown of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration.

INSTALLATION NOTE

Mokara™ is a random match / non-reversible pattern
For specifications and hanging instructions go to: www.denovowall.com

de novo® WALL

Tel: 501-372-3550 Fax: 501-372-3553
www.denovowall.com

Copyright© 2018. All Rights Reserved
Any copying or other use is expressly prohibited
DeNovo Wall is a trademark.

MADE IN USA

