

<b>Physical Properties:</b>	<b>Total Weight</b>	<b>U.S. Units</b>	<b>Metric Units</b>
		20.0 oz./LY	619 G/PLM
		13.3 oz./SY	451 G/PSM
	Fabric Type	Osnaburg	
	Material Width	52/54"	132/137 cm
	Repeat	Horizontal 54" x Vertical 18"	

**Federal Specifications:** DeNovo Vinyl Wallcovering meets or exceeds all requirements of Federal Specification CCC-W-408A-D, W-101 Quality Standard for Polymer Coated Fabric Wallcovering and EN 15102, European Standard for Decorative Wallcoverings.

**Fire Hazard Classification Results:** **ASTM E-84** Tunnel Test: Class A, Flame Spread: 15; Smoke Developed: 20

- Performance Features:**
- Phthalate-free
  - No heavy metals or formaldehyde
  - Printed exclusively with water-based, low VOC inks
  - Microventing for permeability is available on a custom order basis
  - Five year warranty against materials defects

- Environmental Attributes:**
- Ultra-low emitting – Pass rating under CA 01350
  - NSF/ANSI 342 certified for sustainability
  - CA Prop 65 compliant

**Permeability, Moisture and Mold:** Vinyl wallcovering can act as a vapor barrier and consequently should NOT be installed on walls that are susceptible to excessive condensation or moisture infiltration. Breathe Free™ Micro-vented wallcovering from DeNovoWall can be used to help control un-wanted moisture inside a building envelope.

**INSTALLATION NOTE**  
**Rubix Texture™** is a random match / reversible pattern  
 For specifications and hanging instructions go to: [www.denovowall.com](http://www.denovowall.com)