

TOULON LINEN™

TYPE II

PHYSICAL PROPERTIES:

52/54" (132/137 CM) Vinyl Wallcovering, Type II

Total Weight: 20 oz./lin.yard (619 G/PLM)
13.3 oz./sq.yard (451 G/PSM)

Backing: Osnaburg

FEDERAL SPECIFICATIONS:

TOULON LINEN™ as manufactured by DeNovo Wall meets or exceeds G.S.A. Federal Specification CCC-408D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This product has been accepted for use by the City of New York Department of Building.

In addition, this product meets Type II CCC-W-408D requirements for Washability, Scrubbability, Abrasion Resistance and Stain Resistance.

FIRE HAZARD CLASSIFICATION RESULTS:

Tested in accordance with ASTM E-84 Tunnel Test

Class "A" Fire Rated

Flame Spread 15

Smoke Developed 25

Flame Spread
Class 1

Fire Propagation
Class 0

ANTI-MICROBIAL FEATURES:

Vinyl wallcoverings contain bactericides and mildew inhibitors to protect the products from microbiological and mildew growth.

FIVE YEAR WARRANTY AGAINST MANUFACTURING DEFECTS:

Use only adhesives and primers as recommended by the manufacturer.

ENVIRONMENTAL STATEMENT:

We are dedicated to complying with today's environmental issues, and have eliminated all heavy metals such as lead, mercury, cadmium and chromium from our inks and adhesives.

NOTE: The assigned numerical rating and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

All patterns are stocked in 30 linear yard bolts.

INSTALLATION NOTE

TOULON LINEN™ is a reversible pattern.

Design and Materials © Copyright 2003 DeNovo Wall. All Rights Reserved
DeNovo Wall is a colour & design company.
MADE IN USA

de
nōvō®
WALL

Tel: 501-372-3550
Fax: 501-372-3553
www.DenovoWall.com