

Decorative Glass Wall Covering

General Description

Fibreglass wall covering is used to cover walls and other interior surfaces. Product is perfect for new spaces: thanks to its high mechanical properties it prevents cracks from appearing, consequently prolonging the surface lifetime. It is also a performing solution for light renovation: it covers crack and wall irregularities.

Products from Novelio® Nature range are perfect solutions for easy application without important preparation of the wall surface and highly decorative expectations. This range mimics natural wall coverings and products don't need to be painted. Application is as simple as with wall papers

Technical characteristics

Technical Characteristics	
Composition	100 % coated glass fiber
Treated fabric weight (average value)	185 g / m ² (± 8 %)
Loss on ignition (average value minimal)	29 %
Oekotex certificate Standard 100	Product Class III (does not contain any hazardous substance)
Emission in indoor air	A+ (very low)
Fire resistance (EN 13501-1)	Euroclass B, s1-d0 (A1, A2 board)
Recommendation for application	
Quantity of vinyl glue	250 g / m ² (approximate)
Dimensions & Packaging	
Width (individual value)	49 cm / 98 cm (± 1 %)
Roll length (individual value) ⁽¹⁾	10.05 m / 50 m (± 2 %)
Repeat	-
Roll direction ⁽¹⁾	Surface to apply on wall inside of roll
Roll packaging ⁽¹⁾	Collective box, wrapped into plastic foil
Label on box ⁽¹⁾	With installation instructions
Storage conditions	Dry room, storing temperature from -10°C to +50°C. If product is not processed up to one week, it is not recommended to open a package or to remove a package from a roll.
Palette (non-returnable) ⁽¹⁾	1 box: 80 x 120 x 100 cm
Quality Control	
Traceability	Lot no. marked on the small sticker on the roll
Defects marked by label	Maximum 1 point defect / roll ⁽¹⁾
Each defect is balanced by	Adding 50 cm / defect ⁽¹⁾
Product is carefully checked before leaving the factory but should also be checked just before applying. Any claim should be accompanied with roll sticker and a sample featuring the defect.	

(1) Details are described in works standard 0337

Technical Data Sheet

Properties

- Wear-resistant wall covering
- High tensile strength
- Can be repainted
- Excellent Fire resistance
- Breathable
- Environmentally friendly
- Wet stability
- Invisible seams



Edited by:
ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.
Sokolovska 106
CZ – 570 21 Litomyšl
Tel: +420 461 651 111
Fax: +420 461 612 769
www.sg-adfors.com

ADFORS Construction Products Europe reserves the right to change the information given herein without prior notice

Technical Data Sheet N°1
Last update: 20/08/2015