



Opus

Type II

PHYSICAL PROPERTIES

Width	52/54"	132/137 cm
Total Weight	20.0 oz/lin yd	620 g/lin m
Total Weight	13.3 oz/sq yd	451 g/sq m
Vinyl Weight	11.1 oz/sq yd	376 g/sq m
Backing	Polyester/Cotton Osaburg	
Backing Weight	2.2 oz/sq yd	75 g/sq m
Breaking Strength (W x F)	94 x 99 lbs	
Tear Strength (W x F)	47 x 45	

PRODUCT SPECIFICATIONS

Opus as manufactured by Luxes Surfaces, Inc. meets or exceeds G.S.A. Federal Specification CCC-W-408 A/D+A75 for Type II wallcovering using test procedures detailed in Federal Specification CCC-T-191-B. The city of New York Department of Building MEA-205-90M has accepted this product for use.

FIRE HAZARD CLASSIFICATION RESULTS

Tested in accordance with ASTM E-84 Tunnel Test
Class "A" Fire Rated

Flame Spread	10
Smoke Developed	5

The assigned numerical rating and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

PRODUCT FEATURES

- * Contains bactericides and mildew inhibitors to protect the products from microbiological and mildew growth
- * 5 Year Warranty Against Manufacturing Defects
- * Environment friendly products that are Cadmium and Mercury Free

INSTALLATION NOTE

Opus is a reversible/random match pattern

For additional production information please go to www.luxesurfaces.com

Patty Madden ©
All Rights Reserved

Luxe Surfaces, Inc.
501.748.1113
501.978.5694
www.luxesurfaces.com