



CONTRACT UPHOLSTERY with **PreFixx**[®]

LIVE

Product Specifications:

General

Total Wt. - oz./sq. yd. (CFFA-700d)	18.7 ± 10%
Total Wt. - oz./lin. yd. (CFFA-700d)	28
Width (min.) - in. (CFFA-700a)	54"
Gauge (mils)	40 ± 10%
Face Content	PVC

Backing

Construction	Terry Loop Knit
Weight - oz./sq. yd.	3.7
Content	Polyester
Fiber Type	Filament

Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 4.0
	Fill 4.0

Tensile Strength (CFFA-17)

Pounds (min.)	Warp 85
	Fill 75

Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 20
	Fill 27

Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 35
	Fill 30

Performance Testing: meets or exceeds

Abrasion (CFFA-1a)

Wyzenbeek, Wire Screen	60,000 cycles
Wyzenbeek, Cotton Duck	1.3 million cycles

Blocking (CFFA-4)

No. 1

W-Flex (CFFA-10)

25,000 cycles

Crock (CFFA-7)

20 cycles - no stain

UV (CFFA-2)

QUV

650 hours (outdoors)

Mildew Resistance

ASTM G-21	Pass
-----------	------

Cold Crack (CFFA-6a)

-20° F

Flame Retardancy

California Tech. Bulletin 117	Pass
NFPA 701 Small Scale	Pass
Fed. Std. A-A-2950 Supercedes CCC-A-680A	Pass
FAR 25.853A	Pass
Boston Fire Dept. IX-1	Pass
NFPA 260	Pass
FMVSS-302	Pass
UFAC Fabric, Class 1	Pass

Miscellaneous:

Application

Corporate, Hospitality, Healthcare, Marine

Finish

PreFixx[®] Protective Coating

LEVEY INDUSTRIES INC.
 2150 Winston Park Drive Oakville, ONTARIO L6H 5V1 CANADA
 1.800.588.3990 FAX 905.829.8292
 PreFixx is a registered trademark of OMNOVA Solutions Inc.
 Designed and manufactured by OMNOVA Solutions Inc.
 ALL LEVEY PRODUCTS AND SERVICES OFFERED AND SOLD
 ARE SUBJECT TO THE LEVEY STANDARD TERMS AND
 CONDITIONS OF SALE AGREEMENT SET FORTH AT
 www.LeveyUpholstery.com © 2012 LEVEY INDUSTRIES INC.

LeveyUpholstery.com
 1.800.588.3990
 Fax: 905.829.8292