

# SKINTEX SF

## vintage



### GRAFFITI-FREE FAUX LEATHER

#### ::SPECIFICATIONS

- . Width : 54"
- . Nominal thickness : .036 gauge
- . Nominal weight : 20 oz / linear yard
- . Content : Face: 100% polyurethane  
Back: 100% reinforced Pollex™
- . Roll length : 50 yards

#### ::REVOLUTION IN STAIN RESISTANCE\*

- . Exclusive PointeShield™ protection for easy care, stain-free surface.
- 1) Most stains and ballpoint pen marks\*\* can be easily wiped out with a clean dry towel.\*\*\*  
No need to use complicated cleaning procedures.
- 2) Spot clean the spilled area with mild soap and water.
- 3) Rubbing alcohol (isopropyl alcohol)\*\*\*\* can be used to clean any remaining stain. Rinse the cleaned area with clean water and dry with air or lint-free cloth.

#### ::DISINFECTABILITY

SkintexSF™ is formulated to achieve a superior level of disinfectability with a 10:1 bleach solution.

#### ::SUITABLE APPLICATIONS

- . Healthcare
- . Hospitality
- . Contract/Residential interiors

#### ::INNOVATIVE GRAFFITI-FREE FAUX LEATHER

- . Nature friendly, PVC free construction.
- . Passes **Oeko-Tex Standard 100** – the ultimate international benchmark for the safety of the environment and its people.
- . Produced under strict environmental standards and tested free of harmful substances for your well-being.
- . Supple leather touch with exceptional strength and performance.
- . Controlled 4-way stretch for excellent tailorability.

#### ::GENERAL CHARACTERISTICS

- . Superior wear resistance (ASTM D4157 Wyzenbeek) Exceeds 100,000 double rubs by wire screen
- . Anti-Bacterial/Anti-Microbial treatments (AATCC-147)
- . Colorfastness to light (AATCC-16/400 hours)
- . Colorfastness to chlorine bleach (AATCC-3) passes 1:10 & 1:5 bleach dilution test
- . Excellent breaking strength (ASTM D5034)
- . Excellent tear strength (ASTM D2262)
- . Cold crack resistant

#### ::FLAMMABILITY REQUIREMENTS†

- . FMVSS-302
- . CA Bulletin 117 - Class 1
- . UFAC - Class 1
- . NFPA 260 - Class 1
- . BIFMA - Class A
- . IMO A.652(16) 8.2
- . Can be treated to meet FAR Specifications

† This term and any other corresponding data refer to typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

\*General Care: While Skintex SF™ is inherently stain resistant, it is important to keep it clean at all times to maintain the original look and rich feel.

\*\*PointeShield™ does not protect the product against intentional stains such as permanent marker.

\*\*\*Use non-abrasive soft cloth/napkin to avoid scratching of the surface.

\*\*\*\*Caution: Exercise care as alcohols are flammable. Use only small amount and keep clear of any source of ignition. Wear protective gloves during cleaning activities.



WALLCOVERING

• DRY ERASE

• DIGITAL

• ECO-FRIENDLY

• ACOUSTICAL

• SPECIALTY PAINT

**LEVEY WALLCOVERINGS**

[info@leveyindustries.com](mailto:info@leveyindustries.com)



HEAD OFFICE

2150 WINSTON PARK DRIVE  
OAKVILLE ONTARIO L6H 5V1

PHONE: 905.829.8000  
TOLL FREE: 1.800.588.3990  
FAX: 905.829.8292

[WWW.LEVEYINDUSTRIES.COM](http://WWW.LEVEYINDUSTRIES.COM)