





# specifications

## easy install

WriteInfinity Installation Procedure

- Step 1** **For new drywall:** prime wall with high-quality commercial water-based paint primer.  
**For painted walls in good condition:** lightly sand with 150-grit, then clean surface.  
**For walls needing repair or colour change:** apply a high-quality, commercial water-based primer tinted to desired colour. Install this step using 3/8" nap microfibre roller cover provided.
- Step 2** Inspect surface for any unwanted texture. If present, lightly sand surface to ensure it is as smooth as possible.
- Step 3** Install WriteInfinity using 3/8" nap microfibre roller cover provided (note: do not shake or stir) using the installation techniques outlined in detail in the instructions accompanying each kit. Desired coverage is approximately 40 sq ft per each loaded roller cover.
- Step 4** Always inspect your work from all angles to ensure full, even coverage.
- Step 5** Allow to cure for 3 days prior to writing on surface with approved dry erase markers. For complete preparation and installation instructions, please visit [WriteWallsCanada.com](http://WriteWallsCanada.com)

## accessories

WriteInfinity is available with a complete line of accessories and optional finishing products. A wide selection of aluminum trims and marker trays offers convenience, cleanliness and aesthetic appeal. A full list of accessories follows in this catalogue, or visit [WriteWalls.global](http://WriteWalls.global)

Care and maintenance items will ensure your installation endures everyday use. Choose from recommended markers, microfibre cloths, erasers and dry erase cleaners. These items are sold separately and are all searchable online at [WriteWallsCanada.com](http://WriteWallsCanada.com)

## warranty

WriteInfinity is covered by a ten year limited warranty. This warrants that WriteInfinity meets the design criteria noted in our specifications when properly applied per our recommended installation instructions. For more details on the WriteInfinity warranty, please visit [WriteWallsCanada.com](http://WriteWallsCanada.com)

## physical properties

Product Code	Kit Sizes (Coverage)	Application	Dry Time Cure Time	VOC
WWWI-50 WWWI-100 WWWI-200	50sq.ft kit 100sq.ft kit 200sq.ft kit	Single Coat Rolled On	1 hour dry 3 day cure	less than 10g/l
Colour	Scrub Resistance	Sag Resistance	Flame Resistance	
Transparent clear with a glossy finish	greater than 15,000 cycles	less than 3mils	Class A (ASTM E-84)	