



WriteProLite (self adhesive film)

specification guide

3.3 application

- A. Application must be performed by qualified installer.
- B. Do not proceed with installation until all finishing work has been completed in and around the work area.
- C. Install substrates with no gaps, wire seams, or overlaps. Form smooth, wrinkle-free, bubble-free surface for finished installation.
- D. No exposed joints on corners or other "open" type joints permitted.
- E. Verify pattern prior to material acquisition as some part numbers do not allow three-dimensional forming.
- F. Comply with manufacturer's installation instructions applicable to products and applications indicated, except where more stringent requirements apply.
- G. Apply WriteLite over properly prepared substrates.
- H. Remove air bubbles, wrinkles, and blisters. Use approved procedures to prevent the formation of air bubbles, wrinkles, blisters and other defects.

3.4 schedule

Note: When more than one type of WriteLite is specified in this section, it will be necessary to identify where each type is to be used. A schedule may be useful for that purpose, if the types are not to be indicated on the drawing. The following is a suggested format for such a schedule, with an example.

- A. Room:
- B. Fixture:
 - 1. Horizontal Surfaces Exposed to View: Design Category, Product number
 - 2. Vertical Surfaces Exposed to View: Design Category, Product number
 - 3. Semi-exposed Surfaces: Design Category, Product number
 - 4. Shaped Goods: Design Category, Product number
 - 5. Moldings: Design Category, Product number
- C. Shop Drawing Reference: In addition to original A/E elevations, the installation specialist may be asked to provide elevation views of installation surfaces to confirm design intent upon request.



WriteProLite (self adhesive film)

specification guide

3.5 cleaning and protection

- A. Use cleaning methods recommended by architectural surfacing manufacturer for applicable environment.
- B. Protect completed graphic film during remainder of construction period.
- C. Consult with authorized installation specialist for project specifics.

END OF SECTION