

Gilded Masonry

Pattern Series MRE1316 – MRE1320

23.5" Repeat/Straight, Non-Reversible Match
Type II • 20 oz. Mylar
Pompeii Emboss

Physical Properties:

Width: 52"
Total Weight (oz./sq.yd): 13.0 oz.
Total Weight (oz./lin. Yd): 20.0 oz.
Fabric Type: Nonwoven
Backing Fabric Weight: 1.8oz./sq.yard
Average Total Thickness: 16 mils

Federal Specifications:

- This wallcovering meets or exceeds all requirements of G.S.A. Federal Specification CCC-W-408D for Type 2 material.

Fire Hazard Classification Results:

Class A Fire Rated: ASTM E-84 Tunnel Test Flame Spread: Pass Smoke Developed: Pass
Class B Fire Ratings: This wallcovering meets or exceeds requirements of EN 13501, EU Standard for decorative wallcoverings

York Quality Standards

- LEED CONTRIBUTION – Can contribute to LEED for low-emitting materials, adhesives and sealants. Can contribute to LEED for recycled content and LEED for certified wood.
- SUSTAINABLE MATERIALS – Non-woven backing made from wood pulp sourced from managed forests.

Order Requirements:

15 yard minimum purchase. 16+yards, any yard increment available for purchase.

Customs - Available upon request

This wallcovering contains metallic particles and will conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical outlet boxes or light switch boxes. Turn off all electricity to room prior to starting installation.

Please be aware that this wallcovering may interfere with broadcast signals, such as Wi-Fi and radio reception because of the polyester/metal layer in this specific construction.

Vinyl wallcovering has little or no moisture permeability. If the design, construction or maintenance of a building and/or other circumstances allows moisture to accumulate in a wall or wall cavity, vinyl wallcovering can act as a vapor barrier restricting the escape of moisture and increasing the risk of mold growth. Mold and mildew are naturally occurring and are present everywhere in nature. They need only water and organic material [such as wood, paper or plant material] to feed upon and grow. Vinyl wallcovering permeability can be increased through perforation and alternative product constructions with varying degrees of increased permeability depending on the methods used. No wallsurfacing material will prevent mold growth, however, if moisture accumulation is permitted to occur. An experienced professional who is familiar with building conditions and circumstances should be consulted concerning benefits and limitations of vinyl wallcovering.

NOTE: The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by his or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.