


everwalls

everMagnetic60

60" Dry-Erase Wallcovering With Magnetic Capabilities



everMagnetic60 dry erase wallcovering consists of a magnetically receptive high gloss dry erase surface that is more than ideal for an abundance of collaborative needs. **everMagnetic60** has been developed to simultaneously provide exceptional dry eraseability that impedes ghosting while allowing the use of magnets. Backed by a 10-year limited warranty, the durability of **everMagnetic60** makes it suitable for use in various commercial environments.



versatile

- Ideal solution for all collaboration and planning needs
- Magnet receptive core allows for a greater variety of uses
- Applicable to curved walls and columns
- Suitable for public environments that may necessitate heavy use.

uncomplicated

- Provides a seamless writing surface from wall to wall when installed horizontally
- 60" width reduces waste and number of seams when installed floor to ceiling
- Cost effective combined dry erase and magnetic solution
- Use Immediately after install

reliable

- Durable polyester coating is easy to erase and impedes ghosting
- Will not yellow or delaminate over time
- Lightweight for ease of installation and a minimal carbon foot print
- 10-year limited warranty



everMagnetic60 • EV-VM-60

EV-VM-60 technical specs

**Total Weight:**

54 oz / sq yd
24 oz / linear yd

Base Film Weight:

51.25 oz / sq yd

Top Film Weight:

.95 oz / sq yd

Backing Weight:

1.80 oz / sq yd

**Backing:**

100% Polyester

Laminate Thickness:

1mil

Total Thickness:

26mils

Width:

60"

Flame Resistance:

Class A
(ASTM E-84)

Solvent Resistance:

1000 Double Rubs w/
MEK (ASTM D 4752)

Colourfastness:

Class 4.5 - 5 at 200
AFU (AATCC 16E)

Abrasion Resistance:

20,000 Double Rubs /
Wyzenbeek
(ASTM D 3597)

installation

Carefully inspect, before cutting **everMagnetic60** in order to confirm that the correct surface and quantity have been ordered and shipped. For large jobs, rolls should be organized in sequence prior to installation. It is highly important that the entire wall surface is smooth and primed with a high-quality, white latex primer before installing as any wall imperfections will translate to an undesirable finish.

To eliminate seams the writing area, it is recommended that **everMagnetic60** is installed horizontally on the wall space at the desired height. For floor-to-ceiling wall applications, a full width strip should be applied to the wall in the most likely writing area as shown in the 'your wall space' diagram above. Due to the 60" width of **everMagnetic60**, the number of seams in the writing area of the entire wall is reduced from four seams to two.

Further information on preparation and installation instructions can be found at LEVEY.com

accessories

everMagnetic60 is available with a complete line of accessories and optional finishing products. Aluminum trims and marker trays offer convenience, cleanliness and aesthetic appeal.

Care and maintenance items will ensure your installation endures everyday use. Choose from recommended markers, microfibre cloths and dry erase cleaners.

Accessories are sold separately and are all searchable online at LEVEY.com

warranty

everWalls Dry Erase Wallcovering warrants to its purchasers that everWalls Dry Erase products will be free from any defects in material or workmanship and meet the design criteria noted in our specifications when properly applied and installed per our recommended installation instructions.

For further details on the everWalls warranty, please visit LEVEY.com.